



Self-Tapping Screws

Screws for Sheet Metal Applications

Pin T-Drive® (6-Lobe) Countersunk DIN 7982 SIMILAR Type C

Steel / Zinc Plated (CR3)



Dia. mm	2.2	2.9	3.5	3.9	4.2	4.8	5.5	6.3	Dia. mm
Dia. Gauge	2	4	6	7	8	10	12	14	Dia. Gauge
d1 - max	4.30	5.50	6.80	7.50	8.10	9.50	10.80	12.40	d1 - max
k - ref	1.30	1.70	2.10	2.30	2.50	3.00	3.40	3.80	k - ref
s - A/F	-	-	-	-	-	-	-	-	s - A/F
Recess	-	T8	T10	T15	T20	T25	T25	T30	Recess



Scan the QR Code to view technical drawings for this product range
<https://www.lancasterfastener.com/drawings-for-ltabpndrcskzc>

L - Length mm									L - Length ins
4.5									3/16
6.5									1/4
8									5/16
9.5									3/8
13					●				1/2
16									5/8
19					●				3/4
22									7/8
25					●				1
32									1 1/4
38									1 1/2
45									1 3/4
50									2
57									2 1/4
63									2 1/2
70									2 3/4
75									3

● Steel / Zinc Plated (CR3) - preferred and available from stock.

PRODUCT CODE EXAMPLE
 LTABPNDRCSK35160ZC

PRODUCT DESCRIPTION EXAMPLE
 3.5 x 16.0 Pin T-Drive® (6-Lobe) Countersunk DIN 7982 SIMILAR Type C Self-Tapping Screw Steel / Zinc Plated (CR3)