



## Brass Inserts for Plastics



**Brass**  
**Self Colour**  
RoHS 2 Compliant



Further technical data is available on page 264

Unheaded (UHDHEAFIX)									
Thread	M2*	M2.5*	M3	M3.5	M4	M5	M6	M8*	Thread
W mm	3.5	4.4	4.4	5.2	6.1	6.9	8.5	10.0	W mm
N mm	3.1	3.9	3.9	4.7	5.5	6.3	7.9	9.5	N mm
Rec. Hole Size (mm) (-0.0/+0.1)	3.2	4.0	4.0	4.8	5.6	6.4	8.0	9.6	Rec. Hole Size (mm) (-0.0/+0.1)
Min. Wall Thickness (mm)	1.4	1.8	1.8	2.1	2.4	2.8	3.6	5.0	Min. Wall Thickness (mm)
L- Length mm	Bulk Carton Quantity   Small Box Quantity   Weight (KG) per 1,000								L- Length mm
3.9	N/A   1,000   0.16								3.9
5.8		N/A   1,000   0.28	25,000   1,000   0.34						5.8
7.1				25,000   1,000   0.60					7.1
8.1					10,000   1,000   0.99				8.1
9.5						10,000   1,000   1.25			9.5
12.7							2,500   1,000   2.87	N/A   1,000   3.60	12.7
-									-
-									-
-									-
-									-
-									-
-									-
-									-
-									-
-									-
-									-
-									-

Brass Self Colour - preferred and available from stock.

<b>PRODUCT CODE EXAMPLE</b>	<b>PRODUCT DESCRIPTION EXAMPLE</b>
IPMUHDHEAFIX050BRSC	M5 Unheaded Heat-Fix Brass Inserts for Plastics Self Colour

\*Non preferred. UNC & UNF thread sizes available to order. Contact our sales team to enquire for availability. E. & O. E.  
© 2021, Lancaster Fastener Co Ltd. All images are copyright protected.

Carbon Steel Product Ranges

Stainless Steel Product Ranges

Brass Product Ranges

Technical Data