


DIN 7500 Tap-Fix® Screws

Thread Rolling Screws for Metal Applications

Cross Recess (Z) Pan FORM C DIN 7985

Steel / Zinc Plated (CR3) & Steel / Black (CR3)



Dia. D	M2	M2.5	M3	M3.5	M4	M5	M6	M8	Dia. D
Dia. C max	2.06	2.57	3.07	3.58	4.08	5.09	6.10	8.13	Dia. C max
d1 - max	4.00	5.00	6.00	7.00	8.00	10.00	12.00	16.00	d1 - max
k - max	1.72	2.12	2.52	2.82	3.25	3.95	4.75	6.15	k - max
s - A/F	-	-	-	-	-	-	-	-	s - A/F
Recess	1	1	1	2	2	2	3	4	Recess
L - Length mm	 Scan the QR Code to view technical drawings for this product range https://www.lancasterfastener.com/drawings-for-ttmwzpanzc								L - Length mm
4	●	●	●						4
5	●	●	●						5
6	●	●	●	●	● ●	●			6
8	●	●	● ●	●	● ●	●	●		8
10	●	●	●	●	● ●	●	●		10
12			●	●	● ●	●	●		12
14		●	●						14
16		●	●	●	●	●	●		16
18									18
20			●	●	● ●	●	●	●	20
25			●	●	●	●	●		25
30			●		●	●	●		30
35					●	●	●		35
40					●	●	●		40
45									45
50							●		50
-									-



Steel / Zinc Plated (CR3) - preferred and available from stock.



Steel / Black (CR3) - preferred and available from stock.

PRODUCT CODE EXAMPLE

TTMWZPAN40010ZC
TTMWZPAN30008ZN

PRODUCT DESCRIPTION EXAMPLE

M4 x 10 Cross Recess (Z) Pan DIN 7500 FORM C Tap-Fix® Screw Steel / Zinc Plated (CR3)
M3 x 8 Cross Recess (Z) Pan DIN 7500 FORM C Tap-Fix® Screw Steel / Black (CR3)