Tamper Proof Machine Screws

METRIC Series Tamper Proof Screws for Metal Applications

Head Dimensions & Recess Sizes

PROTECTOR 4 - PIN T-DRIVE®

SCREW SIZE	PAN			COUNTERSUNK			BUTTON			COUNTERSUNK		
	DIN 7985 SIMILAR STEEL ZINC PLATED			DIN 965 SIMILAR STEEL ZINC PLATED			ISO 7380 SIMILAR A2 STAINLESS STEEL			DIN 7991 SIMILAR A2 STAINLESS STEEL		
	DIA MAX	DEPTH MAX	RECESS SIZE	DIA MAX	DEPTH REF	RECESS SIZE	DIA MAX	DEPTH MAX	RECESS SIZE	DIA MAX	DEPTH REF	RECESS SIZE
M1.6	3.20	1.42	T5	3.00	0.96	T5	-	-	-	-	-	-
M2	4.00	1.72	T6	3.80	1.20	T6	-	-	-	-	-	-
M2.5	5.00	2.12	T8	4.70	1.50	T8	-	-	-	-	-	-
M3	6.00	2.52	T10	5.60	1.65	T10	5.70	1.65	T10	6.00	1.70	T10
M3.5	7.00	2.82	T15	6.50	1.93	T15	6.60	1.90	T15	7.00	2.00	T15
M4	8.00	3.25	T20	7.50	2.20	T20	7.60	2.20	T20	8.00	2.30	T20
M5	10.00	3.95	T25	9.20	2.50	T25	9.50	2.80	T25	10.00	2.80	T25
M6	12.00	4.75	T30	11.00	3.00	T30	10.50	3.30	T30	12.00	3.30	T30
M8	16.00	6.15	T40	14.50	4.00	T40	14.00	4.40	T40	16.00	4.40	T40

PROTECTOR 7 - PIN HEXAGON

SCREW SIZE	BUTTON			COUNTERSUNK		
	ISO 7380 SIMILAR			DIN 7991 SIMILAR		
	DIA MAX	DEPTH MAX	RECESS SIZE	DIA MAX	DEPTH REF	RECESS SIZE
M3	5.70	1.70	2mm	6.00	1.70	2mm
M3.5	6.60	1.90	2mm	6.50	1.93	2mm
M4	7.60	2.20	2.5mm	8.00	2.30	2.5mm
M5	9.50	2.80	3mm	10.00	2.80	3mm
M6	10.50	3.30	4mm	12.00	3.30	4mm
M8	14.00	4.40	5mm	16.00	4.40	5mm

T-Drive® is a registered trade mark of Lancaster Fastener Co Ltd.
E. & O. E.
© 2021, Lancaster Fastener Co Ltd.