



Dia. D	M2	M2.5	M3	M3.5	M4	M5	M6	M8	Dia. D
Dia. C max	2.06	2.57	3.07	3.58	4.08	5.09	6.10	8.13	Dia. C max
d1 - max	3.80	4.70	5.50	7.30	8.40	9.30	11.30	15.80	d1 - max
k - ref	1.20	1.50	1.65	2.35	2.70	2.70	3.30	4.65	k - ref
s - A/F	-	-	-	-	-	-	-	-	s - A/F
Recess	T6	T8	T10	T15	T20	T25	T30	T45	Recess



Scan the QR Code to view technical drawings for this product range
<https://www.lancasterfastener.com/drawings-for-ttiwtxcskzc>

L - Length mm									L - Length mm
4									4
5									5
6			●		●				6
8			●		●	●			8
10			●		●	●	●		10
12			●		●	●	●		12
14									14
16			●		●	●	●		16
18									18
20			●		●	●	●		20
25						●	●		25
30						●	●		30
35						●			35
40							●		40
45									45
50									50
-									-

● Steel / Zinc Plated (CR3) - preferred and available from stock.

PRODUCT CODE EXAMPLE
TTIWTXCSK60012ZC

PRODUCT DESCRIPTION EXAMPLE
M6 x 12 T-Drive® (6-Lobe) Countersunk DIN 7500 FORM ME ISO 14581 Tap-Fix® Screw Steel / Zinc Plated (CR3)